

\*Always verify tips or orifices you received are the size which you require before using with chemical. Chemical rates need to be obtained from your chemical dealer.

# Turbo TeeJet® Induction Flat Spray Tips



TURBO TEEJET INDUCTION

**Typical Applications:**

Extremely coarse droplet size provides the best drift control possible and is ideal for soil applied and post-emerge systemic products, including dicamba.

**Features:**


- 110° wide angle, air induction, tapered flat spray tip pattern based on the patented outlet orifice design of the original Turbo TeeJet® nozzle.
- Patented orifice design provides large, round passages to minimize plugging.
- Depending on the chemical, produces large air-filled drops through a Venturi air aspirator resulting in less drift.
- All polymer construction for excellent chemical and wear resistance.
- Compact size to prevent tip damage.
- Removable pre-orifice.
- Ideal for use with automatic sprayer controllers.
- Wide operating pressure range: 15-100 PSI.
- Automatic spray alignment with 25598\*-NYR or 11443\*-CELR Quick TeeJet cap and gasket for capacities 015 thru 06.
- Automatic spray alignment with 98579-1-NYR or 114502\*-CELR Quick TeeJet cap and gasket for capacities 08 and 10.

PART NO.	LIST PRICE
<b>SIZES 01-06</b>	
TTI1100##-VP (01-06).....	\$13.47
TTI1100##-VP-C (01-06).....	\$15.39
<b>REQUIRED CAP</b>	
25598*-NYR(current style).....	\$1.41
114443*-NYR(new style).....	\$1.41
<b>SIZES 08-10</b>	
TTI1100##-VP (08-10).....	\$15.75
TTI1100##-VP-CE (08-10).....	\$18.38
<b>REQUIRED CAP</b>	
98579-1-NYR(current style).....	\$2.34
114502*-CELR(new style).....	\$2.34

CATALOG IS LIST PRICE PLEASE APPLY DISCOUNT



\*NOTE\* TeeJet will begin transitioning to a "new" cap lineup. Old style caps are still available and will ship until current inventory is gone.  
 # - Specify Tip Size - C / CE - Includes Quick TeeJet Cap & Gasket  
 \* - Specify Cap Color




Note: Due to pre-orifice design, this tip is not compatible with the 4193A check valve tip strainer.




**TTI11004-VP is the recommended nozzle to use with ROUNDUP READY® XTEND & XTEND MAX**

CONTACT PRODUCT	SYSTEMIC PRODUCT	DRIFT MANAGEMENT
—	EXCELLENT	EXCELLENT



**Optimum Spray Height**



**How to order:**

Specify tip number.

Example:

TTI11004-VP – Polymer with VisiFlo® color-coding

TTI11003-VP-CE – Polymer with VisiFlo color-coding, includes Quick TeeJet cap and gasket

NOZZLE	PSI	DROP SIZE	CAPACITY ONE NOZZLE IN GPM	CAPACITY ONE NOZZLE IN OZ./MIN.	GPA										GALLONS PER 1000 SQ. FT.			
					20"													
					4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH	2 MPH	3 MPH	4 MPH	5 MPH		
TTI110015 (100)	15 UC	0.092	12	6.8	5.5	4.6	3.4	2.7	1.8	1.4	0.31	0.21	0.16	0.13				
	20 UC	0.11	14	8.2	6.5	5.4	4.1	3.3	2.2	1.6	0.37	0.25	0.19	0.15				
	30 UC	0.13	17	9.7	7.7	6.4	4.8	3.9	3.2	2.6	1.9	0.44	0.29	0.22				
	40 UC	0.15	19	11.1	8.9	7.4	5.6	4.5	3.7	3.0	2.2	0.51	0.34	0.26				
	50 UC	0.17	22	12.6	10.1	8.4	6.3	5.0	4.2	3.4	2.5	0.58	0.39	0.29				
TTI11002 (50)	15 UC	0.18	23	13.4	10.7	8.9	6.7	5.3	4.5	3.6	2.7	0.61	0.41	0.31				
	20 UC	0.20	26	14.9	11.9	9.9	7.4	5.9	5.0	4.0	3.0	0.68	0.45	0.34				
	30 UC	0.22	28	16.3	13.1	10.9	8.2	6.5	5.4	4.4	3.3	0.75	0.50	0.37				
	40 UC	0.24	31	17.8	14.3	11.9	8.9	7.1	5.9	4.8	3.6	0.82	0.54	0.41				
	50 UC	0.26	33	19.3	15.4	12.9	9.7	7.7	6.4	5.1	3.9	0.88	0.59	0.44				
TTI110025 (50)	15 UC	0.28	36	21	16.6	13.9	10.4	8.3	6.9	5.5	4.2	0.95	0.63	0.48				
	20 UC	0.30	38	22	17.8	14.9	11.1	8.9	7.4	5.9	4.5	1.0	0.68	0.51				
	30 UC	0.32	41	24	19.0	15.8	11.9	9.5	7.6	6.3	4.8	1.1	0.73	0.54				
	40 UC	0.34	44	25	20.4	16.8	12.6	10.1	8.4	7.2	5.6	1.2	0.79	0.60				
	50 UC	0.36	46	26	21.8	17.8	13.4	10.4	8.7	7.5	5.6	1.3	0.86	0.65				
TTI11003 (50)	15 UC	0.37	47	27	22	18.3	13.7	11.0	9.2	7.7	6.1	1.4	0.91	0.71				
	20 UC	0.38	49	28	23	18.8	14.1	11.3	9.4	7.9	6.2	1.4	0.91	0.71				
	30 UC	0.40	51	30	24	19.8	14.9	11.9	9.9	7.9	5.9	1.4	0.91	0.71				
	40 UC	0.42	54	31	25	21	15.6	12.5	10.4	8.3	6.2	1.4	0.95	0.71				
	50 UC	0.45	58	33	27	22	16.7	13.4	10.6	8.7	6.7	1.5	1.0	0.77				
TTI11004 (50)	15 UC	0.47	60	35	28	23	17.4	14.0	11.6	9.3	7.0	1.6	1.1	0.80				
	20 UC	0.49	63	36	29	23	18.1	14.3	11.9	9.5	7.3	1.6	1.1	0.83				
	30 UC	0.51	65	37	30	24	19.1	14.9	12.5	10.1	7.9	1.6	1.1	0.86				
	40 UC	0.53	68	39	31	26	19.7	15.7	13.1	10.5	7.9	1.8	1.2	0.90				
	50 UC	0.55	71	42	34	28	21	16.9	14.1	11.3	8.5	1.9	1.3	0.97				
TTI11005 (50)	15 UC	0.60	77	45	36	30	22	17.8	14.9	11.9	9.9	2.0	1.4	1.0				
	20 UC	0.63	81	47	37	31	23	18.7	15.6	12.5	9.4	2.1	1.4	1.1				
	30 UC	0.66	84	49	39	33	25	19.6	16.3	13.1	9.8	2.2	1.5	1.1				
	40 UC	0.69	88	51	41	34	26	20	17.1	13.7	10.2	2.3	1.6	1.2				
	50 UC	0.72	92	53	42	35	27	21	17.6	14.1	10.5	2.4	1.6	1.2				
TTI11006 (50)	15 UC	0.75	96	56	45	37	28	22	18.6	14.9	11.1	2.6	1.7	1.3				
	20 UC	0.79	101	59	47	39	29	23	19.6	15.6	11.7	2.7	1.8	1.3				
	30 UC	0.82	105	61	49	41	30	30	20	18.1	14.5	2.8	1.9	1.4				
	40 UC	0.85	109	63	50	42	31	31	21	18.8	15.2	2.9	1.9	1.4				
	50 UC	0.90	115	67	53	45	33	32	22	19.8	16.1	3.0	2.0	1.5				
TTI11008 (50)	15 UC	0.95	122	71	56	47	35	28	24	18.8	14.1	3.2	2.2	1.6				
	20 UC	0.99	127	74	58	49	37	29	25	19.8	14.9	3.3	2.2	1.6				
	30 UC	1.03	132	77	61	51	40	32	30	20.8	15.8	3.4	2.3	1.7				
	40 UC	1.07	137	80	63	53	42	33	31	21.8	16.7	3.5	2.4	1.8				
	50 UC	1.11	142	83	65	55	44	34	32	22.8	17.6	3.6	2.5	1.9				
TTI11010	15 UC	1.15	147	86	67	57	46	36	34	23.8	18.5	3.7	2.6	2.0				
	20 UC	1.19	152	89	71	59	48	37	35	24.8	19.4	3.8	2.7	2.1				
	30 UC	1.23	157	92	73	61	50	39	36	25.8	20.3	3.9	2.8	2.2				
	40 UC	1.27	162	95	75	62	52	41	38	26.8	21.2	4.0	2.9	2.3				
	50 UC	1.31	167	98	77	64	54	43	40	27.8	22.1	4.1	3.0	2.4				

Note: Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C).