

*Always verify tips or orifices you received are the size which you require before using with chemical. Chemical rates need to be obtained from your chemical dealer.



TeeJet® Double Outlet Flat Spray Tips

150° Series Stainless Steel and Brass

Suggested for post-directed application with hose drops.



How to order:

Specify tip number and material.

Example: TQ150-03-SS - Stainless Steel




TQ PART NO.	LIST PRICE
TQ150-##	\$10.91
TQ150-##	\$19.71
## - Specify Tip Size	
TQ150-## - Brass	
TQ150-##-SS - Stainless Steel	
REQUIRED CAP	
25612-* - NYR (current style).....	\$1.24
114441-* - CELR (new style).....	\$1.24
* - Specify Cap Color	
NOTE TeeJet will begin transitioning to a "new" cap lineup. Old style caps are still available and will ship until current inventory is gone.	



TIPO	PSI	CAPACITY ONE NOZZLE IN GPM	GPA Δ 20" Δ											
			4 MPH	5 MPH	6 MPH	7 MPH	8 MPH	9 MPH	10 MPH	12 MPH	14 MPH	16 MPH	18 MPH	
TQ150-01-SS (100)	20	0.071	5.3	4.2	3.5	3.0	2.6	2.3	2.1	1.8	1.5	1.3	1.2	
	25	0.079	5.9	4.7	3.9	3.4	2.9	2.6	2.3	2.0	1.7	1.5	1.3	
	30	0.087	6.5	5.2	4.3	3.7	3.2	2.9	2.6	2.2	1.8	1.6	1.4	
	40	0.10	7.4	5.9	5.0	4.2	3.7	3.3	3.0	2.5	2.1	1.9	1.7	
	50	0.11	8.2	6.5	5.4	4.7	4.1	3.6	3.3	2.7	2.3	2.0	1.8	
TQ150-015-SS (100)	20	0.11	8.2	6.5	5.4	4.7	4.1	3.6	3.3	2.7	2.3	2.0	1.8	
	25	0.12	8.9	7.1	5.9	5.1	4.5	4.0	3.6	3.0	2.5	2.2	2.0	
	30	0.13	9.7	7.7	6.4	5.5	4.8	4.3	3.9	3.2	2.8	2.4	2.1	
	40	0.15	11.1	8.9	7.4	6.4	5.6	5.0	4.5	3.7	3.2	2.8	2.5	
	50	0.17	12.6	10.1	8.4	7.2	6.3	5.6	5.0	4.2	3.6	3.2	2.8	
TQ150-02-SS (100)	20	0.14	10.4	8.3	6.9	5.9	5.2	4.6	4.2	3.5	3.0	2.6	2.3	
	25	0.16	11.9	9.5	7.9	6.8	5.9	5.3	4.8	4.0	3.4	3.0	2.6	
	30	0.17	12.6	10.1	8.4	7.2	6.3	5.6	5.0	4.2	3.6	3.2	2.8	
	40	0.20	14.9	11.9	9.9	8.5	7.4	6.6	5.9	5.0	4.2	3.7	3.3	
	50	0.22	16.3	13.1	10.9	9.3	8.2	7.3	6.5	5.4	4.7	4.1	3.6	
TQ150-03-SS (100)	20	0.21	15.6	12.5	10.4	8.9	7.8	6.9	6.2	5.2	4.5	3.9	3.5	
	25	0.24	17.8	14.3	11.9	10.2	8.9	7.9	7.1	5.9	5.1	4.5	4.0	
	30	0.26	19.3	15.4	12.9	11.0	9.7	8.6	7.7	6.4	5.5	4.8	4.3	
	40	0.30	22	17.8	14.9	12.7	11.1	9.9	8.9	7.4	6.4	5.6	5.0	
	50	0.34	25	20	16.8	14.4	12.6	11.2	10.1	8.4	7.2	6.3	5.6	
TQ150-04-SS (50)	20	0.28	21	16.6	13.9	11.9	10.4	9.2	8.3	6.9	5.9	5.2	4.6	
	25	0.32	24	19.0	15.8	13.6	11.9	10.6	9.5	7.9	6.8	5.9	5.3	
	30	0.35	26	21	17.3	14.9	13.0	11.6	10.4	8.7	7.4	6.5	5.8	
	40	0.40	30	24	19.8	17.0	14.9	13.2	11.9	9.9	8.5	7.4	6.6	
	50	0.45	33	27	22	19.1	16.7	14.9	13.4	11.1	9.5	8.4	7.4	
TQ150-05-SS (50)	20	0.35	26	21	17.3	14.9	13.0	11.6	10.4	8.7	7.4	6.5	5.8	
	25	0.40	30	24	19.8	17.0	14.9	13.2	11.9	9.9	8.5	7.4	6.6	
	30	0.43	32	26	21	18.2	16.0	14.2	12.8	10.6	9.1	8.0	7.1	
	40	0.50	37	30	25	21	18.6	16.5	14.9	12.4	10.6	9.3	8.3	
	50	0.56	42	33	28	24	21	18.5	16.6	13.9	11.9	10.4	9.2	
TQ150-06-SS (50)	20	0.42	31	25	21	17.8	15.6	13.9	12.5	10.4	8.9	7.8	6.9	
	25	0.47	35	28	23	19.9	17.4	15.5	14.0	11.6	10.0	8.7	7.8	
	30	0.52	39	31	26	22	19.3	17.2	15.4	12.9	11.0	9.7	8.6	
	40	0.60	45	36	30	25	22	19.8	17.8	14.9	12.7	11.1	9.9	
	50	0.67	50	40	33	28	25	22	19.9	16.6	14.2	12.4	11.1	
TQ150-08-SS (50)	20	0.57	42	34	28	24	21	18.8	16.9	14.1	12.1	10.6	9.4	
	25	0.63	47	37	31	27	23	21	18.7	15.6	13.4	11.7	10.4	
	30	0.69	51	41	34	29	26	23	20	17.1	14.6	12.8	11.4	
	40	0.80	59	48	40	34	30	26	24	19.8	17.0	14.9	13.2	
	50	0.89	66	53	44	38	33	29	26	22	18.9	16.5	14.7	
TQ150-09-SS (50)	20	0.64	48	38	32	27	24	21	19.0	15.8	13.6	11.9	10.6	
	25	0.71	53	42	35	30	26	23	21	17.6	15.1	13.2	11.7	
	30	0.78	58	46	39	33	29	26	23	19.3	16.5	14.5	12.9	
	40	0.90	67	53	45	38	33	30	27	22	19.1	16.7	14.9	
	50	1.01	75	60	50	43	37	33	30	25	21	18.7	16.7	

TeeJet® Off-Center Flat Spray Tips — Smaller Capacities



TeeJet Off-Center spray tips are commonly installed in double and single swivel nozzle bodies. Because these bodies are adjustable for angular position, a wide spray swath is easily obtained.



OC PART NO.	LIST PRICE
OC-## (Brass)	\$13.33
Sizes: 01, 02, 03, 04, 06, 08, 12, 16	
OC-## (Brass)	\$55.61
Sizes: 10, 20, 30, 40, 60, 80, 125, 150, 250, 300	
OC-SS## (Stainless Steel)	\$19.71
Sizes: 01, 015, 02, 03, 04, 06, 08, 12, 16	
OC-SS## (Stainless Steel)	\$108.15
Sizes: 10, 20, 30, 40, 60, 80, 150, 300	
## - Specify Tip Size	
REQUIRED CAP	
25612-* - NYR (current style).....	\$1.24
114441-* - CELR (new style).....	\$1.24
* - Specify Cap Color	
NOTE TeeJet will begin transitioning to a "new" cap lineup. Old style caps are still available and will ship until current inventory is gone.	

REQUIRED CAP - LARGE SIZES	
CP3819 - Threaded Cap - Brass	\$13.22
CP3819-SS - Threaded Cap-SS	\$37.50
CP4784-AL - Gasket - Aluminum	\$1.93

TIPO	PSI	CAPACITY ONE NOZZLE IN GPM	HEIGHT = 18"						HEIGHT = 24"					
			GPA						GPA					
			"W" IN INCHES	3 MPH	4 MPH	5 MPH	6 MPH	"W" IN INCHES	3 MPH	4 MPH	5 MPH	6 MPH		
OC-01 (100)	30	0.087	58	3.0	2.2	1.8	1.5	65	2.7	2.0	1.6	1.3		
	40	0.10	60	3.3	2.5	2.0	1.7	67	3.0	2.2	1.8	1.5		
	60	0.12	62	3.8	2.9	2.3	1.9	69	3.4	2.6	2.1	1.7		
OC-02 (50)	30	0.17	68	5.0	3.7	3.0	2.5	75	4.5	3.4	2.7	2.2		
	40	0.20	70	5.7	4.2	3.4	2.8	77	5.1	3.9	3.1	2.6		
	60	0.24	72	6.6	5.0	4.0	3.3	78	6.1	4.6	3.7	3.0		
OC-03 (50)	30	0.26	77	6.7	5.0	4.0	3.3	80	6.4	4.8	3.9	3.2		
	40	0.30	80	7.4	5.6	4.5	3.7	83	7.2	5.4	4.3	3.6		
	60	0.37	82	8.9	6.7	5.4	4.5	85	8.6	6.5	5.2	4.3		
OC-04 (50)	30	0.35	91	7.6	5.7	4.6	3.8	93	7.5	5.6	4.5	3.7		
	40	0.40	93	8.5	6.4	5.1	4.3	94	8.4	6.3	5.1	4.2		
	60	0.49	94	10.3	7.7	6.2	5.2	95	10.2	7.7	6.1	5.1		
OC-06 (50)	30	0.52	99	10.4	7.8	6.2	5.2	108	9.5	7.2	5.7	4.8		
	40	0.60	101	11.8	8.8	7.1	5.9	110	10.8	8.1	6.5	5.4		
	60	0.73	102	14.2	10.6	8.5	7.1	111	13.0	9.8	7.8	6.5		
OC-08 (50)	30	0.69	100	13.7	10.2	8.2	6.8	110	12.4	9.3	7.5	6.2		
	40	0.80	102	15.5	11.6	9.3	7.8	112	14.1	10.6	8.5	7.1		
	60	0.98	104	18.7	14.0	11.2	9.3	113	17.2	12.9	10.3	8.6		
OC-12	30	1.04	102	20	15.1	12.1	10.1	113	18.2	13.7	10.9	9.1		
	40	1.20	104	23	17.1	13.7	11.4	115	21	15.5	12.4	10.3		
	60	1.47	105	28	21	16.6	13.9	116	25	18.8	15.1	12.5		
OC-16	30	1.39	132	21	15.6	12.5	10.4	142	19.4	14.5	11.6	9.7		
	40	1.60	138	23	17.2	13.8	11.5	146	22	16.3	13.0	10.8		
	60	1.96	143	27	20	16.3	13.6	148	26	19.7	15.7	13.1		