

\*Always verify tips or orifices you received are the size which you require before using with chemical. Chemical rates need to be obtained from your chemical dealer.

## FullJet® Wide Angle Full Cone Spray Tips


CATALOG IS LIST PRICE PLEASE



FULLJET




FULLJET PART NO.	LIST PRICE
FL-#VS.....	\$14.21
FL-#VC.....	\$9.02
## - Specify Tip Size	
VS - Stainless Steel w/ VisiFlo® Color Coding	
VC - Celcon w/ SS Vane & VisiFlo® Color Coding	
<b>REQUIRED CAP</b>	
25608*-NYR(current style).....	\$1.41
114445*-CELR(new style).....	\$1.41
* - Specify Cap Color	
*NOTE* TeeJet will begin transitioning to a "new" cap lineup. Old style caps are still available and will ship until current inventory is gone.	



### Features:

- Large droplets to reduce drift.
- Excellent spray distribution over a range of pressures 15 - 40 PSI.
- Ideal for use on rigs with sprayer controllers.
- Wide spray angle allows use on 40" spacings.
- Available in VisiFlo® color-coding system in all stainless steel or Celcon with stainless steel vane.
- Can be used with CP25607\*-NY for Quick TeeJet connection.




### Optimum Spray Height

40" Spacing	20" Spacing
20"	20"
30"	30"
40"	39"

FullJet nozzles should be angled 30°-45° from vertical for uniform spray distribution.

\*Wide angle spray nozzle height is influenced by nozzle orientation. The critical factor is to achieve a minimum 30% overlap.



### How to order:

Specify tip number.

Examples:

FL-5VS – Stainless Steel with VisiFlo color-coding

FL-5VC – Celcon with Stainless Steel vane and VisiFlo color-coding

Nozzle	PSI	CAPACITY ONE NOZZLE IN GPM	CAPACITY ONE NOZZLE IN OZ./MIN.	40" Spacing								20" Spacing			
				GPA								GALLONS PER 1000 SQ. FT.			
				3 MPH	4 MPH	5 MPH	6 MPH	7 MPH	8 MPH	10 MPH	2 MPH	3 MPH	4 MPH	5 MPH	
FL-5VS FL-5VC	15	0.34	44	16.8	12.6	10.1	8.4	7.2	6.3	5.0	1.2	0.77	0.58	0.46	
	20	0.38	49	18.8	14.1	11.3	9.4	8.1	7.1	5.6	1.3	0.86	0.65	0.52	
	30	0.46	59	23	17.1	13.7	11.4	9.8	8.5	6.8	1.6	1.0	0.78	0.63	
FL-6.5VS FL-6.5VC	15	0.42	54	21	15.6	12.5	10.4	8.9	7.8	6.2	1.4	0.95	0.71	0.57	
	20	0.48	61	24	17.8	14.3	11.9	10.2	8.9	7.1	1.6	1.1	0.82	0.65	
	30	0.57	73	28	21	16.9	14.1	12.1	10.6	8.5	1.9	1.3	0.97	0.78	
FL-8VS FL-8VC	15	0.51	65	25	18.9	15.1	12.6	10.8	9.5	7.6	1.7	1.2	0.87	0.69	
	20	0.58	74	29	22	17.2	14.4	12.3	10.8	8.6	2.0	1.3	0.99	0.79	
	30	0.70	90	35	26	21	17.3	14.9	13.0	10.4	2.4	1.6	1.2	0.95	
FL-10VS FL-10VC	15	0.67	86	33	25	19.9	16.6	14.2	12.4	9.9	2.3	1.5	1.1	0.91	
	20	0.76	97	38	28	23	18.8	16.1	14.1	11.3	2.6	1.7	1.3	1.0	
	30	0.91	116	45	34	27	23	19.3	16.9	13.5	3.1	2.1	1.5	1.2	
FL-15VS FL-15VC	15	0.97	124	48	36	29	24	21	18.0	14.4	3.3	2.2	1.6	1.3	
	20	1.11	142	55	41	33	27	24	21	16	3.8	2.5	1.9	1.5	
	30	1.32	169	65	49	39	33	28	25	20	4.5	3.0	2.2	1.8	
	40	1.50	192	74	56	45	37	32	28	22	5.1	3.4	2.6	2.0	

**Note:** Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C).